

FLEX CEILING NB WW

Installation :

Project number :

Customer :

Processed by :

Date : 20.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : FLEX CEILING NB WW
Installation :
Project number :
Date : 20.03.2020

1 Luminaire data

1.1 NEMO Studio, FLEX CEILING NB WW (BLFE0401F21WAN)

1.1.1 Data sheet

Manufacturer: NEMO Studio

BLFE0401F21WAN FLEX CEILING NB WW


Luminaire data

Luminaire efficacy : 57.2 lm/W
Classification : A80 ↓100.0% ↑0.0%
CIE Flux Codes : 98 100 100 100 115
UGR 4H 8H : 11.7 / 11.7
Power : 6 W

Equipped with


Quantity : 1
Designation : Source
Colour : 3000 K
Luminous flux : 343 lm
Colour reproduction : 93

Dimensions : Ø33 mm x 70 mm



1.1 NEMO Studio, FLEX CEILING NB WW (BLFE0401F21WAN)

1.1.2 LDC




Manufacturer : NEMO Studio
 Order number : BLFE0401F21WAN
 Luminaire name : FLEX CEILING NB WW
 Equipment : 1 x Source 6 W / 343 lm
 Dimensions : D 33 mm x H 70 mm
 File name : BLFE0401F21WAN.LDT

Luminaire efficacy : 57.2 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 18.0° C0-C180

1.1 NEMO Studio, FLEX CEILING NB WW (BLFE0401F21WAN)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)!$

Manufacturer : NEMO Studio
 Order number : BLFE0401F21WAN
 Luminaire name : FLEX CEILING NB WW
 Equipment : 1 x Source 6 W / 343 lm
 Dimensions : D 33 mm x H 70 mm
 File name : BLFE0401F21WAN.LDT

Luminaire efficacy : 57.2 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 18.0° C0-C180