

FLEX CEILING WW ZOOM - MID

Installation :

Project number :

Customer :

Processed by :

Date : 20.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

1 Luminaire data

1.1 NEMO Studio, FLEX CEILING WW - ZOOM mid (BFLE0401921WAN)

1.1.1 Data sheet

Manufacturer: NEMO Studio

BFLE0401921WAN **FLEX CEILING WW - ZOOM mid**


Luminaire data

Luminaire efficacy : 13.1 lm/W
Classification : A80 ↓100.0% ↑0.0%
CIE Flux Codes : 99 99 100 100 106
UGR 4H 8H : <10.0 / <10.0
Power : 4.2 W

Equipped with


Quantity : 1
Designation : Source
Colour : 3000 K
Luminous flux : 55 lm
Colour reproduction : 93

Dimensions : Ø33 mm x 80 mm



1.1 NEMO Studio, FLEX CEILING WW - ZOOM mid (BFLE0401921WAN)

1.1.2 LDC




Manufacturer : NEMO Studio
 Order number : BFLE0401921WAN
 Luminaire name : FLEX CEILING WW - ZOOM mid
 Equipment : 1 x Source 4.2 W / 55 lm
 Dimensions : D 33 mm x H 80 mm
 File name : BFLE0401921WAN - mid.LDT

Luminaire efficacy : 13.1 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 22.6° C0-C180

1.1 NEMO Studio, FLEX CEILING WW - ZOOM mid (BFLE0401921WAN)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)!$

Manufacturer : NEMO Studio
 Order number : BFLE0401921WAN
 Luminaire name : FLEX CEILING WW - ZOOM mid
 Equipment : 1 x Source 4.2 W / 55 lm
 Dimensions : D 33 mm x H 80 mm
 File name : BFLE0401921WAN - mid.LDT

Luminaire efficacy : 13.1 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 22.6° C0-C180