

FLEX CEILING MB WW

Installation :

Project number :

Customer :

Processed by :

Date : 20.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : FLEX CEILING MB WW
Installation :
Project number :
Date : 20.03.2020

1 Luminaire data

1.1 NEMO Studio, FLEX CEILING MB WW (BFLE0401421WAN)

1.1.1 Data sheet

Manufacturer: NEMO Studio

BFLE0401421WAN

FLEX CEILING MB WW


Luminaire data

Luminaire efficacy : 51.3 lm/W
Classification : A80 ↓100.0% ↑0.0%
CIE Flux Codes : 97 99 100 100 117
UGR 4H 8H : 15.0 / 15.0
Power : 6 W

Equipped with


Quantity : 1
Designation : Source
Colour : 3000 K
Luminous flux : 308 lm
Colour reproduction : 93

Dimensions : Ø33 mm x 70 mm



1.1 NEMO Studio, FLEX CEILING MB WW (BFLE0401421WAN)

1.1.2 LDC




Manufacturer : NEMO Studio
 Order number : BFLE0401421WAN
 Luminaire name : FLEX CEILING MB WW
 Equipment : 1 x Source 6 W / 308 lm
 Dimensions : D 33 mm x H 70 mm
 File name : BFLE0401421WAN.LDT

Luminaire efficacy : 51.3 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 26.8° C0-C180

1.1 NEMO Studio, FLEX CEILING MB WW (BFLE0401421WAN)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)!$

Manufacturer : NEMO Studio
 Order number : BFLE0401421WAN
 Luminaire name : FLEX CEILING MB WW
 Equipment : 1 x Source 6 W / 308 lm
 Dimensions : D 33 mm x H 70 mm
 File name : BFLE0401421WAN.LDT

Luminaire efficacy : 51.3 lm/W (A80)
 Light distribution : rotationally symmetric
 Beam Angle : 26.8° C0-C180