

RIGA INDOOR 1m WW

Installation :

Project number :

Customer :

Processed by :

Date : 24.03.2020

The following values are based on precise calculations performed on calibrated lamps and luminaires, and their configurations, whereby gradual, unavoidable deviations can occur in practice. All guarantee claims are excluded for the specified data.

This exclusion of liability applies irrespective of the legal grounds for both damages and consequential damages suffered by users and third parties.

Object : RIGA INDOOR 1m WW
Installation :
Project number :
Date : 24.03.2020

1 Luminaire data

1.1 NEMO Studio, RIGA INDOOR WW 1m (MRIG0450006WRE)

1.1.1 Data sheet

Manufacturer: NEMO Studio

MRIG0450006WRE

RIGA INDOOR WW 1m


Luminaire data

Luminaire efficacy : 111.25 lm/W
Classification : A30 ↓99.8% ↑0.2%
CIE Flux Codes : 41 73 93 100 105
UGR 4H 8H : 25.3 / 28.3
Power : 4 W

Equipped with


Quantity : 1
Designation : Source
Colour : 3050 K
Luminous flux : 445 lm
Colour reproduction : 80

Dimensions : 1030 mm x 15 mm x 8 mm



1.1 NEMO Studio, RIGA INDOOR WW 1m (MRIG0450006WRE)

1.1.2 LDC




Manufacturer : NEMO Studio
 Order number : MRIG0450006WRE
 Luminaire name : RIGA INDOOR WW 1m
 Equipment : 1 x Source 4 W / 445 lm
 Dimensions : L 1030 mm x W 15 mm x H 8 mm
 File name : MRIG0450006WRE.LDT

Luminaire efficacy : 111.25 lm/W (A30)
 Light distribution : sym. to C0-C180 / C90-C270
 Beam Angle : 122.6° C0-C180
 141.3° C90-C270

1.1 NEMO Studio, RIGA INDOOR WW 1m (MRIG0450006WRE)

1.1.3 Cone diagram



Note: The illuminance is calculated with $I(\gamma=0)!$

Manufacturer	: NEMO Studio	Luminaire efficacy	: 111.25 lm/W (A30)
Order number	: MRIG0450006WRE	Light distribution	: sym. to C0-C180 / C90-C270
Luminaire name	: RIGA INDOOR WW 1m	Beam Angle	: 122.6° C0-C180
Equipment	: 1 x Source 4 W / 445 lm		: 141.3° C90-C270
Dimensions	: L 1030 mm x W 15 mm x H 8 mm		
File name	: MRIG0450006WRE.LDT		