

# NEMO

## Luminaire


Code KEM LWW 54  
Name Kepler Minor Downlight 69W

## Measurement

Code KM112022  
Name Kepler Minor Downlight 69W

Luminaire Flux	4000 lm	Luminaire Power	69.0 W	Efficacy	57.971 lm/W	Efficiency	100.00%
Source Flux	4000 lm	Maximum value	222.84 cd/klm	Position	C=200.00 G=2.00	CG	Asymmetrical
Rectangular Luminaire		Length	840 mm	Width	840 mm	Height	330 mm
Rectangular Luminous Area		Length	840 mm	Width	840 mm	Height	330 mm
Horizontal Luminous Area		0.705600 m2		Emitting area on Plane 180°		0.277200 m2	
Emitting area on Plane 0°		0.277200 m2		Emitting area on Plane 270°		0.277200 m2	
Emitting area on Plane 90°		0.277200 m2		Glare area at 76°		0.439666 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		27-01-2000		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4000 lm	
Operator				Rated Voltage			
Temperature				Rated Current			
Humidity				Photocell			
Notes							

Luminaire Sources						
Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty	
	Led	Led	4000.00	69.00	1	
C.I.E.	35 63 84 89 100	D DIN 5040	B21			
F UTE	0.89 H + 0.11 T	B NBN	BZ 6			



ULOR 11.49 %  
DLOR 88.51 %  
RN 11.49 %

